



**X10**

## ZYCOO SIP Paging Gateway

ZYCOO X10 SIP paging gateway is SIP enabled multifunctional IP audio device dedicated for industry users. It can convert voice streams from a SIP paging system or IP PBX system to analogue sounds for background music, public address, intercom, etc. Based on the compact hardware design, open standard SIP protocol support, rich functionality and high performance. Industry users can customize the X10 SIP paging gateway into any desired form of intercom devices or paging speakers. With which can be widely used for smart and safe city applications, to increase the efficiency of communication and information sharing, as a result to improve public safety and citizen welfare.

## Feature Highlights



### Built-in Amplifier

Built-in amplifier rated at 2x10W dual-channel output, passive loudspeakers can be connected directly for stereo audio output, no external amplifier is needed.



### Stereo Audio

Music can be streamed from ZYCOO IP Audio Center using streamed media to the X10 SIP paging gateway for local decoding and playback, high definition stereo audio quality is guaranteed.



### Two-way Intercom

Support 2 programmable "press-to-talk" switch buttons, with an external speaker and microphone, it can do two-way intercom calls for emergency or consulting purposes.



### HD Audio Codecs

Support G.722 wideband audio codec, provides clear and intelligible voice speech for the intercom calls. With the high audio reproduction ability and clarity, quality of communication is guaranteed.



### Compatible with Third-party SIP Server

With SIP protocol support, the X10 SIP paging gateways can be easily integrated with existing third-party SIP servers. SIP paging or intercom calling using your existing phone system.



### Door Magnet Control

The X10 SIP paging gateways is equipped with built-in relay switch, which can be used for door magnet control or other devices to be controlled with dry contact signal. The invoke of dry contact signal can be digital input signal from sensors, DTMF signal or call status.



### Automatic Control

The X10 SIP paging gateway supports processing the external sensor or other devices' digital input signal, to invoke dry contact signal output for door magnet control, automated emergency calling, automated emergency alarm, etc.



### Auto Provisioning

ZYCOO IP Audio Center auto provisioning support, large-scale installations (local or remote) will be effort and time-saving.



### Power over Ethernet (PoE)

Standard PoE (IEEE802.3at) support, simple and easy installation with a single network cable. Large-scale installation will be extremely easy and timesaving.



### X10 External Audio Collection

With the 3.5mm audio input jack, it can collect external audio sources from devices such as mobile phones, computers, mp3, etc. and playback through the corresponding devices.



### Various Peripherals Support

Various peripherals can be integrated, like IP camera, smoke sensors, infrared sensors, door magnet, sound and light alarm which can be used for public safety and security purposes.



### No Server Relies

Support Multicast and Peer-to-peer (P2P) to share data between devices without a central server while the devices use under the same local network.



### Multi SIP Accounts

Support three lines SIP accounts, in which users may register the endpoint in more than one system for achieving different functionality purposes.

## Specifications

<b>Audio Interfaces</b>		<b>X10</b>
Amplifier Output	2x10W, 8Ω (4 pins)	
Headset Output	3.5mm Jack	
Microphone	3.5mm Jack	
<b>Other Interfaces</b>		
Power Input	DC 12V-3A Jack	
Volume Control	VOL+ and VOL-, press both to announce IP address	
Ethernet	ETH0+ETH1, 10/100Mbps, ETH0 with PoE IEEE 802.3at enabled	
Call button	Support 2 call buttons (switch button)	
Call button LED	Support 2 call button LED indicators	
Digital level output	N/A	
Digital level input	5V Max	
Dry Contact	NO/NC contacts, max AC 125V-1A, DC 60V-1A	
<b>Audio</b>		
Audio Codecs	G.722, G.711 A-law, G.711 U-law, Opus	
Music Streaming	MP3 sampling rate 8 – 48KHz, bit rate 64 – 320kbps, mono or Stereo	
<b>Protocols</b>		
Protocols	SIP(RFC3261), HTTP, TCP/IP, SSL, DNS, SNTP, NTP, RTSP, RTP, RTCP, TCP, UDP, MQTT, ICMP, DHCP, ARP, SSH	
<b>Administration</b>		
Configuration	Web interface or auto provisioning server	
Provision method	MQTT IoT Protocol	
<b>Mechanical Properties</b>		
Processor	ARM Cortex-A35	
RAM	128MB DDR3	
Storage	128MB SLC Flash	
<b>Environment</b>		
Working Environment	-20°C ~ +50°C	
Storage Environment	-40°C ~ +75°C	
Humidity	10% ~ 95%RH Non-condensing	
<b>Other</b>		
Dimension	153*76*33mm	
Weight	303g	
RST Key	Press and hold for 5 seconds to reset to factory defaults	
LED Indicator	PWR power indicator, SYS system indicator	



We Focus · We Deliver

---

No. 1602, 16th Floor, Building No. 599, Century City South Road, High-tech Zone, Chengdu, Sichuan Province, China

+86 28 85337096

[zycoo@zycoo.com](mailto:zycoo@zycoo.com)