

# Video Conferencing Speakerphone

Yealink CP50 is a professional-grade conference room speaker that integrates noise reduction, echo cancellation, and reverberation removal. It features Yealink's audio solutions and is equipped with an upgraded 8-unit omnidirectional microphone array for 360 ° pickup. It effectively eliminates conference room noises, including reverberation, echo, air conditioning vibration, and keyboard typing. Paired with high-quality full-frequency speakers, it delivers clearer and more natural human voice. It supports daisy-chaining for expanded conference spaces and flexible deployment, ensuring stable calls and clear video conferences, providing an immersive audio communication experience.



# **Key Feature**

#### High-quality sound, smooth calls

Equipped with Yealink audio algorithms and an 8-unit omnidirectional microphone array, CP50 provides 360° sound pickup and effectively eliminates environmental noise. The high-quality full-frequency speakers make the sound clearer and more natural.

## Full-duplex

Full-duplex allows for clear bidirectional communication, ensuring smooth and clear conversations during meetings.

### Multi-unit cascading for distributed scenarios

Up to 8 devices can be cascaded via POE cable, meeting the pickup and amplification needs of different sizes of conference rooms, effectively avoiding sudden changes in sound volume and ensuring smooth communication (When cascading 4 or more CP50 devices with CPE40, it is necessary to choose the optional DC 48V/2A power adapter).

### Integrated meeting control

Features integrated mute, volume +, volume -, and Bluetooth physical buttons, synchronizing with meeting software status for easy control of the meeting.

### Multiple connectivity options

USB port for connecting to PC; internet port for connecting to video conferencing endpoint hosts; Bluetooth for connecting to mobile devices.

#### Wired content sharing/BYOD

When used with M500 and other devices, it can directly connect to a PC via Type-C for instant content sharing. When used UVC85 and other devices, it can directly connect to a PC via Type-C for utilizing conference room audio-visual peripherals during computer-based meetings.

# **Specifications**

#### **Power Supply**

• Average power consumption: 7.2W

• Power input:

- DC power adapter: DC48V/0.7A or DC48V/2A

- PoE power: Not supported

• Power output:

- USB external power: Not supported

#### Microphone

• Built-in 8-microphone array

• Pickup distance: 6m

Signal-to-noise ratio: 71.8dB SPL @1kHz, A-wight-ed

 Maximum sound pressure level: 122dB SPL @ 1KHz, THD<1%</li>

• Sensitivity:  $-38dB \pm 1dB @ 1KHz (0dB = 1V/Pa)$ 

• Frequency response: 100Hz~12KHz

• Sampling rate: 48KHz

• Bit depth: 16bit

#### Speaker

Built-in 1 x 4W speaker

• Maximum output power: 6W

• Effective power (RMS): 4W

Sensitivity: 100dB SPL +/-3dB SPL @0.1m, 1W

• Frequency response: 100Hz~20KHz

### **Audio Cascading**

 When equipped with a standard 48V0.7A power supply, the CP50 can cascade up to 3 CPE40 units.

• With an optional 48V2A power supply, the CP50 can cascade up to 7 CPE40 units.

#### Audio Technology

- 360° omnidirectional pickup
- Full-duplex technology
- Automatic gain control
- Second-generation AI intelligent audio technology:
- Intelligent noise cancellation
- Intelligent echo cancellation
- Intelligent reverberation cancellation

#### Hardware Interfaces

- Interface
  - 1×DC48V power interface
  - 1×Codec port: Connects to UVC cameras (e.g., UVC85) or VC main units (e.g., MeetingEye 500)
  - 1×Audio port: Connects to CPE40
  - $1 \times Type$ -C port: Connects to a computer
- Wireless
  - Wireless Bluetooth 5.0, stable transmission dis tance of 10m (unobstructed environment)

#### **Environmental**

• Operating humidity: 10~95%, non-condensing

• Operating temperature: 0~40°C

• Storage temperature: -30°C~70°C

### Package Features

- Package includes:
- CP50
- DC power adapter(standard 48V/0.7A, optional 48V/2A)
- 7.5m Ethernet cable
- 1.2m dual-head USB-C cable
- Cable ties\*2
- Cable cover\*1; Screw\*2
- Quick Start Guide
- Quantity:4

• N.W/CTN: 6.1 kg

• G.W/CTN: 6.7 kg

Dimensions: 665 \*221 \* 252 mm
Giftbox Size: 241 \* 216 \* 162 mm
Carton Size: 665 \* 221 \* 252 mm



#### **About Yealink**

Yealink (Stock Code: 300628) is a global-leading provider of Unified Communication & Collaboration Solutions specialized in video conferencing, voice communications, and collaboration, dedicated to helping every person and organization embrace the power of "Easy Collaboration, High Productivity".

With best-in-class quality, innovative technology, and user-friendly experiences, Yealink is one of the best providers in more than 140 countries and regions, ranks No.1 in the global market share of IP Phone, and is the Top 5 leader in the video conferencing market (Frost & Sullivan, 2021).

For more information about Yealink, click here.

#### Copyright

Copyright © 2024 YEALINK(XIAMEN) NETWORK TECHNOLOGY CO., LTD.

All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Yealink(Xiamen) Network Technology CO., LTD.

#### **Technical Support**

Visit Yealink WIKI (http://support.yealink.com/) for firmware downloads, product documents, FAQ, and more. For better service, we sincerely recommend you to use Yealink Ticketing system (https://ticket.yealink.com) to submit all your technical issues.



YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.

Web: www.yealink.com

Addr: No.666 Hu'an Rd, Huli District Xiamen City, Fujian, P.R.C

Copyright@2024 Yealink Inc. All right reserved.